



US006526650B2

(12) **United States Patent**  
**Gaskin**

(10) Patent No.: **US 6,526,650 B2**  
(45) Date of Patent: **Mar. 4, 2003**

(54) **FEED HEAD**

(75) Inventor: **Ian Gaskin, Kent (GB)**

(73) Assignee: **BAS Components Limited (GB)**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/739,290**

(22) Filed: **Dec. 19, 2000**

(65) **Prior Publication Data**

US 2001/0022016 A1 Sep. 20, 2001

(51) Int. Cl.<sup>7</sup> ..... **B23Q 15/00; B23P 21/00**

(52) U.S. Cl. .... **29/715; 29/716; 29/798; 29/809**

(58) Field of Search ..... **29/432, 715, 716, 29/798, 809, 243.529, 243.517**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,946,478 A \* 3/1976 Goodsmith et al. .... 29/798  
3,971,116 A \* 7/1976 Goodsmith et al. .... 29/798  
4,164,072 A \* 8/1979 Shinjo ..... 29/720  
4,242,793 A \* 1/1981 Matthews et al. .... 29/798  
4,348,796 A \* 9/1982 Smallegan ..... 29/432  
4,442,584 A \* 4/1984 Smallegan ..... 29/432  
4,998,659 A \* 3/1991 Goodsmith et al. .... 227/7

5,360,137 A \* 11/1994 Shinjo et al. .... 221/238  
5,619,788 A \* 4/1997 Schmidt ..... 29/798  
5,887,339 A \* 3/1999 Schmidt  
6,401,331 B1 \* 6/2002 Mizuno ..... 29/771  
6,442,830 B1 \* 9/2002 Vrana ..... 29/715  
6,446,833 B1 \* 9/2002 Morishima et al. .... 221/268

**FOREIGN PATENT DOCUMENTS**

GB A1474766 5/1973

\* cited by examiner

Primary Examiner—Gregory M. Vidovich

Assistant Examiner—Essama Omgba

(74) Attorney, Agent, or Firm—Finnegan, Henderson, Farabow, Garrett & Dunner, L.L.P.

(57) **ABSTRACT**

A feed head has a delivery path along which nuts are fed to a pressing station in the feed head, the pressing station having a pressing die which is reciprocated transversely to the delivery path under the action of a press to fasten a nut to a sheet metal member. A cam is provided to reciprocate the pressing die manually to facilitate clearance of blockages in the feed head, and also to hold the pressing die in its lowered position to allow operation of the press without operating the die. A sensor for detecting nuts at the pressing station is positioned on the end of the delivery path, enabling a narrower feed head design. A electrical coupling and nut delivery tube are integrated to facilitate connection in confined spaces.

**6 Claims, 2 Drawing Sheets**

